Page: 1 of 7

Revision: 10/19/2015 Supersedes Revision: 03/06/2015

1. Product and Company Identification

Product Code: 00073A

Product Name: Twin-Chem NO ODOR MASTIC REMOVER

Company Name: TWIN-CHEMICALS, INC. **Phone Number:** 6175 Hickory Flat Highway (800)442-4958

6175 Hickory Flat Highway Suite 110-344

Canton, GA 30755

Web site address: www.twinchemicals.com
Email address: sales@twinchemicals.com

Emergency Contact: CERTS (Health & Environment only) (800)552-3787 **Information:** Sales & Information - (800)442-4958

2. Hazards Identification

Flammable Liquids, Category 3
Acute Toxicity: Skin, Category 4
Skin Corrosion/Irritation, Category 2
Aspiration Toxicity, Category 2
Acute Toxicity: Inhalation, Category 4







GHS Signal Word: Warning

GHS Hazard Phrases: H226 - Flammable liquid and vapor.

H305 - May be harmful if swallowed and enters airways.

H312 - Harmful in contact with skin.

H315 - Causes skin irritation. H332 - Harmful if inhaled.

GHS Precaution Phrases: P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P240 - Ground/bond container and receiving equipment. P233 - Keep container tightly

closed.

P243 - Take precautionary measures against static discharge.

P261 - Avoid breathing mist/vapours/spray. P264 - Wash hands thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/protective clothing/eye protection.

GHS Response Phrases: P301+310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated

clothing. Rinse skin with water/shower.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P312 - Call a POISON CENTER or doctor/physician if you feel unwell.

P331 - Do NOT induce vomiting.

P332+313 - If skin irritation occurs, get medical advice/attention. P362 - Take off contaminated clothing and wash before re-use.

GHS Storage and Disposal

P403+235 - Store in cool/well-ventilated place.

Phrases: P501 - Dispose of contents/container to a waste facility according to local regulations.

Page: 2 of 7

Revision: 10/19/2015 Supersedes Revision: 03/06/2015

Potential Health Effects (Acute and Chronic):

Prolonged or repeated skin contact may cause defatting and dermatitis.

Chronic: May cause liver and kidney damage. Sophisticated modeling has clearly proven that 2-butoxyethanol does not build up in the body under any kinds of normal use.

Inhalation: Harmful if inhaled. May cause narcotic effects in high concentration. May cause lung

damage. May cause central nervous system effects such as nausea and headache.

Material is irritating to mucous membranes and upper respiratory tract.

Skin Contact: Causes skin irritation. Causes symptoms similar to those of inhalation. Skin sensitization

testing with human volunteers produced negative results. A skin notation is not recommended by ACGIH, based on estimates from physiologically based

pharmacokinetic models which indicate that, even in worst-case dermal-exposure

scenarios, 2-butoxyethanol is not absorbed in amounts sufficient to cause red blood cell

hemolysis in humans. May cause skin irritation.

Eye Contact: Causes redness and pain. Causes severe eye irritation.

Ingestion: Aspiration hazard. May cause irritation of the digestive tract. Harmful if swallowed. May

cause gastrointestinal irritation with nausea, vomiting and diarrhea. Prolonged or repeated exposure may cause allergic reactions in certain sensitive individuals.

3. Composition/Information on Ingredients

CAS#	Hazardous Components (Chemical Name)	Concentration
64742-47-8	Hydrotreated light distillate (petroleum)	80.0 -90.0 %
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, Glycol Ether EB}	10.0 -15.0 %
9016-45-9	Poly(oxy-1,2-ethanediyl), .alpha(nonylphenyl)omegahydr {Nonylphenol Ethoxylate}	3.0 -6.0 %

4. First Aid Measures

Emergency and First Aid

Procedures:

In Case of Inhalation: If inhaled, remove to fresh air. If breathing is difficult, give oxygen. Get medical aid

immediately. Remove from exposure and move to fresh air immediately.

In Case of Skin Contact: In case of contact, flush skin with plenty of water. Remove contaminated clothing and

shoes. Get medical aid if irritation develops and persists. Wash clothing before reuse.

In Case of Eye Contact: In case of contact, immediately flush eyes with plenty of water for a t least 15 minutes.

Get medical aid immediately.

In Case of Ingestion: Potential for aspiration if swallowed. Get medical aid immediately. Never give anything

by mouth to an unconscious person. If vomiting occurs naturally, have victim lean forward. Call a poison control center. If swallowed, wash out mouth with water provided

person is conscious. Call a physician.

Signs and Symptoms Of

Exposure:

Exposure can cause: Nausea, headache, and vomiting.

Note to Physician: None known.

Page: 3 of 7

Revision: 10/19/2015 Supersedes Revision: 03/06/2015

5. Fire Fighting Measures

Flash Pt: 79.00 C Method Used: Cleveland Open Cup

Explosive Limits: LEL: 0.6 UEL: 7.0

Autoignition Pt: > 231.00 C

Suitable Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or appropriate foam. Suitable:

Fire Fighting Instructions: As in any fire, wear a self-contained breathing apparatus in pressure-demand,

MSHA/NIOSH (approved or equivalent), and full protective gear. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Use

water spray to keep fire-exposed containers cool. Will burn if involved in a fire. Combustible liquid and vapor. Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Specific

Hazard(s):

Flammable Properties and

Hazards:

Hazardous Combustion

Products:

6. Accidental Release Measures

Protective Precautions, Protective Equipment and Emergency Procedures: Hand: Compatible chemical-resistant gloves. Always use a NIOSH or European Standard EN 149 approved respirator when necessary. Eye protection is recommended.

Environmental Precautions:

Do not discharge directly into the environment or into the sewer system.

Steps To Be Taken In Case Material Is Released Or Spilled: Use proper personal protective equipment as indicated in Section 8.

Spills/Leaks: Avoid runoff into storm sewers and ditches which lead to waterways. Clean up spills immediately, observing precautions in the Protective Equipment section. Remove all sources of ignition. Provide ventilation. Do not let this chemical enter the

environment. PROCEDURE(S) OF PERSONAL PRECAUTION(S)

Wear respirator, chemical safety goggles, rubber boots, and heavy rubber gloves.

Methods for cleaning up.

Absorb on sand or vermiculite and place in closed containers for disposal. Ventilate area and wash spill site after material pickup is complete.

7. Handling and Storage

Precautions To Be Taken in Handling:

Wash thoroughly after handling. Use with adequate ventilation. Avoid contact with eyes, skin, and clothing. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep container tightly closed. Avoid ingestion and inhalation. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Keep away from heat, sparks and flame. Do not ingest or inhale.

User Exposure: Do not breathe vapor.

Precautions To Be Taken in

Storing:

Keep away from sources of ignition. Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible substances.

8. Exposure Controls/Personal Protection

CAS#	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
64742-47-8	Hydrotreated light distillate (petroleum)		TLV: 200 mg/m3	
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, Glycol Ether EB}	PEL: 50 ppm	TLV: 20 ppm	
9016-45-9	Poly(oxy-1,2-ethanediyl), .alpha(nonylphenyl)omegahydr {Nonylphenol Ethoxylate}			

Page: 4 of 7

Revision: 10/19/2015 Supersedes Revision: 03/06/2015

Respiratory Equipment

(Specify Type):

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European

Standard EN 149. Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi- purpose combination (US) or type ABEK (EN 14387)

respirator cartridges as a backup to engineering controls. Hand: Compatible

chemical-resistant gloves.

Eye Protection: Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166. Chemical safety goggles.

Protective Gloves: Wear appropriate protective gloves to prevent skin exposure.

Other Protective Clothing: Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls

(Ventilation etc.):

Facilities storing or utilizing this material should be equipped with an eyewash facility and

a safety shower. Use adequate ventilation to keep airborne concentrations low. Use explosion-proof ventilation equipment. Use only under a chemical fume hood. Safety

shower and eye bath.

Work/Hygienic/Maintenance

Wash thoroughly after handling.

Practices:

9. Physical and Chemical Properties

Physical States: [] Gas [X] Liquid [] Solid

Appearance and Odor: Clear liquid.

solvent odor.

pH: NP

Freezing Point: < -70.00 C

Boiling Point: 210.00 C - 288.00 C

Flash Pt: 79.00 C Method Used: Cleveland Open Cup

Evaporation Rate: > 5 (BuAC=1)

Flammability (solid, gas):

Explosive Limits: LEL: 0.6 UEL: 7.0

Vapor Pressure (vs. Air or

mm Hg):

.05 MM HG

Vapor Density (vs. Air = 1): NA

Specific Gravity (Water = 1): 0.800 - 0.820 at 20.0 C

Density: NP
Solubility in Water: Nil
Saturated Vapor NA

Concentration:

Octanol/Water Partition

Coefficient:

Percent Volatile: > 94.0 % by weight.

Autoignition Pt: > 231.00 C

Decomposition Temperature:

Viscosity: Water thin

Page: 5 of 7

Revision: 10/19/2015 Supersedes Revision: 03/06/2015

10. Stability and Reactivity

Stability: Unstable [] Stable [X]

Conditions To Avoid -

ignition sources, Incompatible materials.

Instability:

Incompatibility - Materials To Strong acids. Strong bases, Oxidizing agents.

Avoid:

Hazardous Decomposition or Carbon monoxide, oxides of sulfur.

Byproducts:

Possibility of Hazardous

Will occur [] Will not occur [X]

Reactions:

Conditions To Avoid - Hazardous Reactions:

11. Toxicological Information

Toxicological Information: Epidemiology: No information found.

Teratogenicity: No information available. Reproductive Effects: Mutagenicity:

Neurotoxicity:

Carcinogenicity/Other

Information:

CAS# 64742-47-8: Not listed by ACGIH, IARC, NTP, or CA Prop 65. CAS# 111-76-2:

ACGIH: A3 - Confirmed animal carcinogen with unknown relevance to humans.

California: Not listed. NTP: Not listed. IARC: Not listed.

CAS#	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
64742-47-8	Hydrotreated light distillate (petroleum)	n.a.	n.a.	A4	n.a.
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, Glycol Ether EB}	n.a.	3	A3	n.a.
9016-45-9	Poly(oxy-1,2-ethanediyl), .alpha(nonylphenyl)omegahydr {Nonylphenol Ethoxylate}	n.a.	n.a.	n.a.	n.a.

12. Ecological Information

General Ecological Information:

Environmental: TERRESTRIAL FATE: Based on a recommended classification scheme, an estimated Koc value of 67,, determined from an experimental log Kow and a recommended regression-derived equation, indicates that ethylene glycol mono-n-butyl ether is expected to have high mobility in soil. An estimated BCF value of 2.5 was calculated for ethylene glycol mono-n-butyl ether, using an experimental log Kow of 0.83 and a recommended regression-derived equation. According to a recommended classification scheme, this BCF value suggests that bioconcentration in aquatic organisms is low.

Physical: No information found.

Other: An estimated BCF value of 2.5,, from an experimental log Kow, suggests that ethylene glycol mono-n-butyl ether bioconcentration in aquatic organisms will be low,

according to a recommended classification scheme. ELIMINATION.

Page: 6 of 7

Revision: 10/19/2015 Supersedes Revision: 03/06/2015

13. Disposal Considerations

Waste Disposal Method:

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

RCRA P-Series: None listed.

RCRA U-Series: None listed. Empty container may be recycled or disposed of as solid sanitary waste. Do not reuse container. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Environmentally hazardous substance, liquid, n.o.s

(applies to single containers of more than 119 gallons -

smaller containers are not regulated)

NOT REGULATED FOR DOMESTIC TRANSPORT.

DOT Hazard Class: UN/NA Number:

LAND TRANSPORT (Canadian TDG):

TDG Shipping Name: Environmentally hazardous substance, liquid, n.o.s

(applies to single containers of more than 119 gallons -

smaller containers are not regulated)

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Non-Hazardous for Air Transport: Non-hazardous for air transport.

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS # 64742-47-8	Hazardous Components (Chemical Name) Hydrotreated light distillate (petroleum)	S. 302 (EHS) No	S. 304 RQ No	S. 313 (TRI) No
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, Glycol Ether EB}	No	No	Yes-Cat. N230
9016-45-9	Poly(oxy-1,2-ethanediyl), .alpha(nonylphenyl)omegahydr {Nonylphenol Ethoxylate}	No	No	No
CAC#	Hazardous Components (Chemical Name)	Other US EPA or S	tata l iete	
CAS#	riazardous Components (Chemical Name)	Other US EPA OF S	tate Lists	
64742-47-8	Hydrotreated light distillate (petroleum)		o; CWA NPDES: No;	TSCA: Yes -
	,	CAA HAP,ODC: No Inventory; CA PRO	o; CWA NPDES: No; DP.65: No o; CWA NPDES: No;	

Page: 7 of 7

Revision: 10/19/2015 Supersedes Revision: 03/06/2015

16. Other Information

Revision Date: 10/19/2015

HMIS:

Additional Information About

Hazard Rating System:

This Product:

Company Policy or

Disclaimer:

THE INFORMATION CONTAINED HEREIN is based upon available information at the time of preparation and isbelieved to be accurate but is not warranted to be so. Users are advised to confirm in advance of need that the information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or any other user proximately caused by the material if misused or if reasonable safety procedures are not adheared to as stipulated in the data sheet and on the prduct label. Furthermore, vendor assumes no responsibility for injury or damage caused by abnormal use of this material even if reasonable safety measures are followed.